

# **MigratoryData Client API for iOS**

Developer's Guide and Reference Manual

*June 14, 2015*



## Copyright Information

Copyright © 2007-2015 Migratory Data Systems. ALL RIGHTS RESERVED.

THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THE DOCUMENT. MIGRATORY DATA SYSTEMS MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT DESCRIBED IN THIS DOCUMENT AT ANY TIME.

# Contents

<b>1</b>	<b>Developer's Guide</b>	<b>1</b>
1.1	Overview	1
1.2	Creating iOS clients for MigratoryData Server	1
1.2.1	Step 1 - Include the library.	1
1.2.2	Step 2 - Define the listener class to get the real-time messages and status notifications.	1
1.2.3	Step 3 - Specify the list of MigratoryData servers where to connect to.	1
1.2.4	Step 4 Subscribe to subjects and publish messages	2
1.2.5	Step 5 - Handle the real-time messages and status notifications.	2
1.3	Examples	2
<b>2</b>	<b>Hierarchical Index</b>	<b>3</b>
2.1	Class Hierarchy	3
<b>3</b>	<b>Class Index</b>	<b>5</b>
3.1	Class List	5
<b>4</b>	<b>File Index</b>	<b>7</b>
4.1	File List	7
<b>5</b>	<b>Class Documentation</b>	<b>9</b>
5.1	MigratoryDataClient Class Reference	9
5.1.1	Detailed Description	10
5.1.2	Method Documentation	10
5.1.2.1	setLogType:	10
5.1.2.2	setListener:	10
5.1.2.3	setServers:	10
5.1.2.4	subscribe:	11
5.1.2.5	subscribeWithConflation:conflationTimeMillis:	12
5.1.2.6	unsubscribe:	12
5.1.2.7	setEncryption:	12
5.1.2.8	setEntitlementToken:	13
5.1.2.9	getSubjects	13
5.1.2.10	setServersDownBeforeNotify:	13

5.1.2.11	publish:	13
5.1.2.12	pause	13
5.1.2.13	resume	14
5.1.2.14	dispose	14
5.2	MigratoryDataField Class Reference	14
5.2.1	Detailed Description	14
5.2.2	Method Documentation	15
5.2.2.1	init:value:	15
5.2.2.2	getName	15
5.2.2.3	getValue	15
5.3	<MigratoryDataListener> Protocol Reference	15
5.3.1	Detailed Description	15
5.3.2	Method Documentation	15
5.3.2.1	onMessage:	15
5.3.2.2	onStatus:info:	16
5.4	MigratoryDataMessage Class Reference	17
5.4.1	Detailed Description	17
5.4.2	Method Documentation	17
5.4.2.1	init:content:	17
5.4.2.2	init:content:fields:	17
5.4.2.3	init:content:closure:	18
5.4.2.4	init:content:fields:closure:	18
5.4.2.5	getSubject	18
5.4.2.6	getContent	18
5.4.2.7	getFields	18
5.4.2.8	getClosure	19
5.4.2.9	isSnapshot	19
<b>6</b>	<b>File Documentation</b>	<b>21</b>
6.1	src/MigratoryDataClient.h File Reference	21
6.1.1	Detailed Description	21
6.2	src/MigratoryDataField.h File Reference	21
6.2.1	Detailed Description	21
6.3	src/MigratoryDataGlobals.h File Reference	21
6.3.1	Detailed Description	22
6.3.2	Function Documentation	22
6.3.2.1	NS_ENUM	22
6.3.3	Variable Documentation	23
6.3.3.1	NOTIFY_SERVER_UP	23
6.3.3.2	NOTIFY_SERVER_DOWN	23

---

6.3.3.3	NOTIFY_DATA_SYNC	23
6.3.3.4	NOTIFY_DATA_RESYNC	23
6.3.3.5	NOTIFY_SUBSCRIBE_ALLOW	23
6.3.3.6	NOTIFY_SUBSCRIBE_DENY	23
6.3.3.7	NOTIFY_PUBLISH_DENIED	24
6.3.3.8	NOTIFY_PUBLISH_NO_SUBSCRIBER	24
6.3.3.9	NOTIFY_PUBLISH_OK	24
6.3.3.10	NOTIFY_PUBLISH_FAILED	24
6.4	src/MigratoryDataListener.h File Reference	24
6.4.1	Detailed Description	24
6.5	src/MigratoryDataMessage.h File Reference	24
6.5.1	Detailed Description	25
<b>Index</b>		<b>25</b>



# Chapter 1

## Developer's Guide

This guide includes the following sections:

- [Overview](#)
- [Creating iOS clients for MigratoryData Server](#)
- [Examples](#)

### 1.1 Overview

This application programming interface (API) contains all the necessary operations for connecting to a cluster of one or more MigratoryData servers, subscribing to subjects, getting real-time messages for the subscribed subjects, and publishing real-time messages.

Before reading this manual, it is recommended to read *MigratoryData Architecture Guide* ([PDF](#), [HTML](#)).

### 1.2 Creating iOS clients for MigratoryData Server

A typical API usage is as follows:

#### 1.2.1 Step 1 - Include the library.

Include the headers of the API located in the folder `lib` of this API package.

Add the `lib` folder to the *Include Directories* of your iOS application.

The API library is available in the folder `lib` of this API package. Add the `lib` folder to the *Library Directories* of your iOS application. Also, add the API library itself to the list of *Library Dependencies* of your iOS application.

#### 1.2.2 Step 2 - Define the listener class to get the real-time messages and status notifications.

The listener should implement the [MigratoryDataListener](#) interface.

Use the API call [MigratoryDataClient::setListener](#): to attach your listener implementation.

#### 1.2.3 Step 3 - Specify the list of MigratoryData servers where to connect to.

Use the API method [MigratoryDataClient::setServers](#): to specify one or more MigratoryData servers to which your iOS client will connect to. In fact, the iOS client will connect to only one of the MigratoryData servers in this list.

But, defining two or more MigratoryData servers is recommended to achieve fail-over (and horizontal scaling / load balancing). Supposing the MigratoryData server - to which the iOS client connected - goes down, then the API will automatically reconnect that client to another MigratoryData server in the list.

#### 1.2.4 Step 4 Subscribe to subjects and publish messages

Use the API method [MigratoryDataClient::subscribe](#): to subscribe to subjects and use the API method [MigratoryDataClient::publish](#): to publish messages.

#### 1.2.5 Step 5 - Handle the real-time messages and status notifications.

Handle the messages received for the subscribed subjects as well as the status notifications in your listener implementation defined at Step 2 above.

### 1.3 Examples

Examples built with this API are available in the folder `examples` of this API package; start with the README file which explains how to compile and run them.



# Chapter 2

## Hierarchical Index

### 2.1 Class Hierarchy

This inheritance list is sorted roughly, but not completely, alphabetically:

- <MigratoryDataListener> . . . . . 15
- NSObject
  - MigratoryDataClient . . . . . 9
  - MigratoryDataField . . . . . 14
  - MigratoryDataMessage . . . . . 17



# Chapter 3

## Class Index

### 3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

- [MigratoryDataClient](#)  
This class implements all the necessary operations for connecting to a cluster of one or more MigratoryData servers, subscribing to subjects, getting real-time messages for the subscribed subjects, and publishing real-time messages . . . . . 9
- [MigratoryDataField](#)  
Represent a message field . . . . . 14
- [<MigratoryDataListener>](#)  
Implementations of this interface can handle the real-time messages received for the subscribed subjects as well as various status notifications . . . . . 15
- [MigratoryDataMessage](#)  
Represent a message . . . . . 17



# Chapter 4

## File Index

### 4.1 File List

Here is a list of all documented files with brief descriptions:

- src/[MigratoryDataClient.h](#)  
    Include the declaration of the [MigratoryDataClient](#) class . . . . . 21
- src/[MigratoryDataField.h](#)  
    Include the declaration of the [MigratoryDataField](#) class . . . . . 21
- src/[MigratoryDataGlobals.h](#)  
    Include global constants and typedefs . . . . . 21
- src/[MigratoryDataListener.h](#)  
    Include the declaration of the [MigratoryDataListener](#) class . . . . . 24
- src/[MigratoryDataMessage.h](#)  
    Include the declaration of the [MigratoryDataMessage](#) class . . . . . 24




## Chapter 5

# Class Documentation

### 5.1 MigratoryDataClient Class Reference

This class implements all the necessary operations for connecting to a cluster of one or more MigratoryData servers, subscribing to subjects, getting real-time messages for the subscribed subjects, and publishing real-time messages.

Inheritance diagram for MigratoryDataClient:



#### Instance Methods

- (id) - [init](#)  
*Create a [MigratoryDataClient](#) object.*
- (void) - [setLogType:](#)  
*Configure the logging level.*
- (void) - [setListener:](#)  
*Attach a [MigratoryDataListener](#) for handling real-time messages and status notifications.*
- (void) - [setServers:](#)  
*Specify a cluster of one or more MigratoryData servers to which the client will connect to.*
- (void) - [subscribe:](#)  
*Subscribe to one or more subjects.*
- (void) - [subscribeWithConflation:conflationTimeMillis:](#)  
*Subscribe to one or more subjects with conflation.*
- (void) - [unsubscribe:](#)  
*Unsubscribe from one or more subjects.*
- (void) - [setEncryption:](#)  
*Configure whether to use SSL/TLS encryption when connecting to a MigratoryData server.*
- (void) - [setEntitlementToken:](#)  
*Assign an authorization token to the client.*
- (NSArray \*) - [getSubjects](#)  
*Return the list of subscribed subjects.*
- (void) - [setServersDownBeforeNotify:](#)

Define the number of failed attempts to connect to one or more MigratoryData servers before triggering a status notification `NOTIFY_SERVER_DOWN`.

- (void) - [publish](#):  
Publish a message.
- (void) - [pause](#):  
Pause the API operation.
- (void) - [resume](#):  
Resume the API operation.
- (void) - [dispose](#):  
Disconnect from the connected MigratoryData server and dispose the resources used by the connection.

### 5.1.1 Detailed Description

This class implements all the necessary operations for connecting to a cluster of one or more MigratoryData servers, subscribing to subjects, getting real-time messages for the subscribed subjects, and publishing real-time messages.

### 5.1.2 Method Documentation

#### 5.1.2.1 -(void) setLogType: (LogType) logLevel

Configure the logging level.

It is advisable to configure this first if you want to log as much as possible. The default log level is `LogType.LOG_INFO`.

##### Parameters

<i>logLevel</i>	The logging verbosity ( <code>LogType.LOG_ERROR</code> , <code>LogType.LOG_INFO</code> , <code>LogType.LOG_DEBUG</code> or <code>LogType.LOG_TRACE</code> ); by default <code>LogType.LOG_INFO</code> is configured.
-----------------	--

#### 5.1.2.2 -(void) setListener: (NSObject< MigratoryDataListener > \*) listener

Attach a [MigratoryDataListener](#) for handling real-time messages and status notifications.

##### Parameters

<i>listener</i>	An instance of a class which implements the <a href="#">MigratoryDataListener</a> interface
-----------------	---

#### 5.1.2.3 -(void) setServers: (NSArray \*) servers

Specify a cluster of one or more MigratoryData servers to which the client will connect to.

If you specify two or more MigratoryData servers, then all these MigratoryData servers should provide the same level of data redundancy, by making available for subscription the same set of subjects. This is required for achieving (weighted) load balancing, failover, and guaranteed message delivery of the system. In this way, the MigratoryData servers of the `servers` list form a *cluster*.

For example, to connect to a cluster formed of two MigratoryData servers installed at the addresses `p1.example.com` and `p2.example.com`, and configured to accept clients on the standard HTTP port 80, the following code can be used:

```
NSArray *servers = [NSArray arrayWithObjects:@"p1.example.com:80", @"p2.example.com:80"];
[client setServers:servers];
```

To achieve load-balancing, the API connects the client to a MigratoryData server chosen randomly from the



`servers` list. In this way, the load is balanced among all the members of the cluster.

Moreover, the API supports weighted load-balancing. This feature is especially useful if the MigratoryData servers in the cluster are installed on machines with different capacities. You can assign to each member of the cluster a *weight* ranging from 0 to 100. This weight assignment is a hint provided to the API to select with a higher probability a MigratoryData server with a higher weight either initially when the client connects to the cluster or later during a failover reconnection.

Supposing the address `p1.example.com` corresponds to a machine that is twice more powerful than the machine having the address `p2.example.com`, then you can assign to `p1.example.com` a weight 100 and to `p2.example.com` a weight 50 by prefixing each address with the assigned weight as follows:

```
NSArray *servers = [NSArray arrayWithObjects:@"100 p1.example.com", @"50 p2.example.com"];
[client setServers:servers];
```

The API assigns a default weight 100 to the addresses not prefixed with a specific weight.

To achieve failover, if the connection between the client and a MigratoryData server is broken, then the API will automatically detect the failure and will select another MigratoryData server from the `servers` list. If the client fails to connect to the new selected server, a status notification `NOTIFY_SERVER_DOWN` will be triggered (unless you modify the number of failed attempts with `MigratoryDataClient::setServersDownBeforeNotify:`), and a new MigratoryData server in the cluster will be selected again and again until the client will be able to connect to one of the MigratoryData servers in the cluster. When successfully connected, the API will trigger a status notification `NOTIFY_SERVER_UP`.

Furthermore, if guaranteed message delivery is enabled, then the potential messages published for a subscribed subject during the failover period, will be automatically retrieved from the cache of the MigratoryData server to which the client reconnects to and a status notification `NOTIFY_DATA_SYNC` will be triggered for that subject.

If, for example, the failover period is abnormally long, and the client is not able to retrieve, after a failover reconnection, the messages published during the failover period for one of its subscribed subjects, then the API will retrieve only the most recent message available for that subject and will trigger a `NOTIFY_DATA_RESYNC` status notification for that subject, the client behaving as a new client which connects to the cluster at the moment of the failover reconnection.

For a complete discussion related to load balancing, failover, and guaranteed message delivery features see the *MigratoryData Architecture Guide* ([PDF](#), [HTML](#)).

#### Parameters

<i>servers</i>	An array of strings where each string represents the network address (IP address or DNS domain name and its corresponding port) of a MigratoryData server, optionally prefixed by a weight ranging from 0 to 100. If the weight prefix is not provided to an address, then the API will automatically assign to that address a default weight 100.
----------------	--

#### 5.1.2.4 `-(void) subscribe: (NSArray *) subjects`

Subscribe to one or more subjects.

Subscribe for real-time messages having as subjects the strings provided in the `subjects` parameter.

As an example, supposing messages are market data updates having as subjects stock names. Then, to subscribe for the messages having as subjects `/stocks/NYSE/IBM` and `/stocks/Nasdaq/MSFT` the following code will be used:

```
NSMutableArray *subjects = [NSMutableArray new];
[subjects addObject:@"/stocks/NYSE/IBM"];
[subjects addObject:@"@/stocks/Nasdaq/MSFT"];
[client subscribe:subjects];
```

The subjects are strings having a particular syntax. See the Chapter "Concepts" in the *MigratoryData Architecture Guide* ([PDF](#), [HTML](#)) to learn about the syntax of the subjects.

## Parameters

<i>subjects</i>	An array of strings representing subjects.
-----------------	--

## 5.1.2.5 - (void) subscribeWithConflation: (NSArray \*) subjects conflationTimeMillis:(int) conflationMillis

Subscribe to one or more subjects with conflation.

Subscribe for real-time messages having as subjects the strings provided in the `subjects` parameter.

If the optional parameter `conflationMillis` is used, then for each subject in the `subjects` list given in argument, its messages will be aggregated in the MigratoryData server and published every `conflationMillis` milliseconds as aggregated data (containing only the latest value for that subject and its latest field values). The value of `conflationMillis` should be a multiple of 100 milliseconds, otherwise the MigratoryData server will round it to the nearest value multiple of 100 milliseconds (e.g. 76 will be rounded to 0, 130 will be rounded to 100, 789 will be rounded to 700, ...). If the value of `conflationMillis` is 0 (or is rounded to 0), then no conflation will apply, and data publication will be message-by-message with no message aggregation.

As an example, supposing the messages are market data updates having as subjects stock names. Then, to subscribe for the messages having as subjects `/stocks/NYSE/IBM` and `/stocks/Nasdaq/MSFT` using 1-second conflation the following code will be used:

```
NSMutableArray *subjects = [NSMutableArray new];
[subjects addObject: "/stocks/NYSE/IBM"];
[subjects addObject: @"/stocks/Nasdaq/MSFT"];
[client subscribeWithConflation:subjects conflationTimeMillis:1000];
```

The subjects are strings having a particular syntax. See the Chapter "Concepts" in the *MigratoryData Architecture Guide* ([PDF](#), [HTML](#)) to learn about the syntax of the subjects.

## Parameters

<i>subjects</i>	An array of strings representing subjects.
<i>conflationMillis</i>	An optional argument defining the number of milliseconds used to aggregate ("conflate") the messages for each subject in the <code>subjects</code> list; default value is 0 meaning that no conflation will apply, and data publication will be message-by-message with no message aggregation.

## 5.1.2.6 - (void) unsubscribe: (NSArray \*) subjects

Unsubscribe from one or more subjects.

Unsubscribe from the subscribed subjects provided in the `subjects` parameter.

## Parameters

<i>subjects</i>	An array of strings representing subjects.
-----------------	--

## 5.1.2.7 - (void) setEncryption: (BOOL) encryption

Configure whether to use SSL/TLS encryption when connecting to a MigratoryData server.

When using encryption you have to connect to the ports of the MigratoryData servers that are configured to listen for encrypted connections. See the parameter `ListenEncrypted` in the *MigratoryData Configuration Guide* ([PDF](#), [HTML](#)).

## Parameters

<i>encryption</i>	Determine whether the client connects to the MigratoryData server using an encrypted SSL/TLS connection
-------------------	---

## 5.1.2.8 - (void) setEntitlementToken: (NSString \*) token

Assign an authorization token to the client.

To define which users of your application have access to which subjects, you will first have to set the parameter `Entitlement` on `true` in the configuration file of the MigratoryData server ,see the parameter `Entitlement` in the *MigratoryData Configuration Guide* ([PDF](#), [HTML](#)).

Then, you will have to use the entitlement-related part of the MigratoryData Extension API to allow or deny certain users to subscribe / publish to certain subjects.

## Parameters

<i>token</i>	A string representing an authorization token.
--------------	---

## 5.1.2.9 - (NSArray \*) getSubjects

Return the list of subscribed subjects.

## Returns

The list of strings representing the subscribed subjects.

## 5.1.2.10 - (void) setServersDownBeforeNotify: (int) n

Define the number of failed attempts to connect to one or more MigratoryData servers before triggering a status notification `NOTIFY_SERVER_DOWN`.

## Parameters

<i>n</i>	The number of the failed attempts to connect to one or more MigratoryData servers before triggering a status notification <code>NOTIFY_SERVER_DOWN</code> ; default value is 1.
----------	---

## 5.1.2.11 - (void) publish: (MigratoryDataMessage \*) message

Publish a message.

If the message includes a closure data, then a status notification will be provided via `MigratoryDataListener::on-Status:info`: to inform whether the message publication has been successful or failed.

## Parameters

<i>message</i>	A <code>MigratoryDataMessage</code> message
----------------	---

## 5.1.2.12 - (void) pause

Pause the API operation.

If the application built with this API library enters into background, then it is recommended to use this API call. It will disconnect the user from the MigratoryData sever but will preserve the user's context (including the cluster

definition and subscribed subjects) in order to reconnect to the cluster later when the API method [MigratoryDataClient::resume](#) is called.

Moreover, if the cluster is configured with guaranteed message delivery, then when the user will reconnect to the cluster using [MigratoryDataClient::resume](#), it will get all messages published since the [MigratoryDataClient::pause](#) method was called, provided however that the duration between the time when [MigratoryDataClient::pause](#) method was called and the [MigratoryDataClient::resume](#) method was called is less than the value defined by the parameter `CacheExpireTime` of the MigratoryData server (see details about this parameter in *MigratoryData Configuration Guide* ([PDF](#), [HTML](#))).

#### 5.1.2.13 - (void) resume

Resume the API operation.

If the application was paused with the [MigratoryDataClient::pause](#) method, then this API call will attempt to reconnect the user to the cluster. Also, if guaranteed message delivery is enabled, this method also retrieves all messages published since the [MigratoryDataClient::pause](#) has been called provided that the duration between the time when [MigratoryDataClient::pause](#) method was called and the [MigratoryDataClient::resume](#) method was called is smaller than the value defined by the parameter `CacheExpireTime`.

This method will be typically used when the application switches to foreground.

#### 5.1.2.14 - (void) dispose


Disconnect from the connected MigratoryData server and dispose the resources used by the connection.

This method should be called when the connection is no longer necessary.

## 5.2 MigratoryDataField Class Reference

Represent a message field.

Inheritance diagram for MigratoryDataField:



### Instance Methods

- (id) - [init:value:](#)  
*Create a [MigratoryDataField](#) object.*
- (NSString \*) - [getName](#)  
*Get the field name.*
- (NSString \*) - [getValue](#)  
*Get the field value.*

#### 5.2.1 Detailed Description

Represent a message field.

## 5.2.2 Method Documentation

### 5.2.2.1 -(id) init: (NSString \*) name value:(NSString \*) value

Create a [MigratoryDataField](#) object.

#### Parameters

<i>name</i>	The field name
<i>value</i>	The field value

### 5.2.2.2 -(NSString \*) getName

Get the field name.

#### Returns

A string representing the field name.

### 5.2.2.3 -(NSString \*) getValue

Get the field value.

#### Returns

A string representing the field value.

## 5.3 <MigratoryDataListener> Protocol Reference

Implementations of this interface can handle the real-time messages received for the subscribed subjects as well as various status notifications.

### Instance Methods

- (void) - [onMessage:](#)  
*This method handles the real-time messages received from a MigratoryData server for the subscribed subjects.*
- (void) - [onStatus:info:](#)  
*This method handles the status notifications.*

### 5.3.1 Detailed Description

Implementations of this interface can handle the real-time messages received for the subscribed subjects as well as various status notifications.

Use the API method [MigratoryDataClient::setListener:](#) to register your listener implementation.

## 5.3.2 Method Documentation

### 5.3.2.1 -(void) onMessage: (MigratoryDataMessage \*) message

This method handles the real-time messages received from a MigratoryData server for the subscribed subjects.

## Parameters

<i>message</i>	An object of type <a href="#">MigratoryDataMessage</a> .
----------------	--

## 5.3.2.2 - (void) onStatus: (NSString \*) status info:(NSString \*) info

This method handles the status notifications.

The possible values of the `status` parameter are:

- [NOTIFY\\_SERVER\\_UP](#) indicates that the client successfully connected to the MigratoryData server provided in the detail information of the status notification
- [NOTIFY\\_SERVER\\_DOWN](#) indicates that the client was not able to connect to the MigratoryData server provided in the detail information of the status notification
- [NOTIFY\\_DATA\\_SYNC](#) indicates that, after a failover reconnection, the client successfully synchronized the subject given in the detail information of the status notification. Moreover, the client received the messages published during the failover period for this subject.
- [NOTIFY\\_DATA\\_RESYNC](#) indicates that, after a failover reconnection, the client successfully synchronized the subject given in the detail information of the status notification. However, the client have not received the potential messages published during the failover period for this subject, the client behaving like a new client which just connected to the MigratoryData server.
- [NOTIFY\\_SUBSCRIBE\\_ALLOW](#) indicates that the client – identified with the token given in the argument of [MigratoryDataClient::setEntitlementToken:](#) – is allowed to subscribe to the subject provided in the detail information of the status notification
- [NOTIFY\\_SUBSCRIBE\\_DENY](#) indicates that the client – identified with the token given in the argument of [MigratoryDataClient::setEntitlementToken:](#) – is not allowed to subscribe to the subject provided in the detail information of the status notification
- [NOTIFY\\_PUBLISH\\_OK](#) indicates that the client successfully published the message having the closure data provided in the detail information of the status notification
- [NOTIFY\\_PUBLISH\\_FAILED](#) indicates that the client was unable to publish the message having the closure data provided in the detail information of the status notification
- [NOTIFY\\_PUBLISH\\_DENIED](#) indicates that the client was unable to publish the message having the closure data provided in the detail information of the status notification because the client – identified with the token given in the argument of [MigratoryDataClient::setEntitlementToken:](#) – is not allowed to publish on the subject of the message
- [NOTIFY\\_PUBLISH\\_NO\\_SUBSCRIBER](#) indicates that the client was unable to publish the message having the closure data provided in the detail information of the status notification because there is no client subscribed to the subject of the message


## Parameters

<i>status</i>	The type of the status notification (see the possible values above).
<i>info</i>	The detail information of the status notification.

## 5.4 MigratoryDataMessage Class Reference

Represent a message.

Inheritance diagram for MigratoryDataMessage:



### Instance Methods

- (id) - [init:content:](#)  
Create a [MigratoryDataMessage](#) object.
- (id) - [init:content:fields:](#)  
Create a [MigratoryDataMessage](#) object.
- (id) - [init:content:closure:](#)  
Create a [MigratoryDataMessage](#) object.
- (id) - [init:content:fields:closure:](#)  
Create a [MigratoryDataMessage](#) object.
- (NSString \*) - [getSubject](#)  
Get the subject of the message.
- (NSString \*) - [getContent](#)  
Get the content of the message.
- (NSArray \*) - [getFields](#)  
Get the fields of the message.
- (NSString \*) - [getClosure](#)  
Get the closure of the message.
- (bool) - [isSnapshot](#)  
Test whether the message is a snapshot message or not.

### 5.4.1 Detailed Description

Represent a message.

### 5.4.2 Method Documentation

#### 5.4.2.1 - (id) init: (NSString \*) subject content:(NSString \*) content

Create a [MigratoryDataMessage](#) object.

#### Parameters

<i>subject</i>	The subject of the message
<i>content</i>	The content of the message

#### 5.4.2.2 - (id) init: (NSString \*) subject content:(NSString \*) content fields:(NSArray \*) fields

Create a [MigratoryDataMessage](#) object.

## Parameters

<i>subject</i>	The subject of the message
<i>content</i>	The content of the message
<i>fields</i>	The fields of the message

5.4.2.3 - (id) init: (NSString \*) *subject* content:(NSString \*) *content* closure:(NSString \*) *closure*

Create a [MigratoryDataMessage](#) object.

## Parameters

<i>subject</i>	The subject of the message
<i>content</i>	The content of the message
<i>closure</i>	The closure of the message

5.4.2.4 - (id) init: (NSString \*) *subject* content:(NSString \*) *content* fields:(NSArray \*) *fields* closure:(NSString \*) *closure*

Create a [MigratoryDataMessage](#) object.

## Parameters

<i>subject</i>	The subject of the message
<i>content</i>	The content of the message
<i>fields</i>	The fields of the message
<i>closure</i>	The closure of the message

5.4.2.5 - (NSString \*) *getSubject*

Get the subject of the message.

## Returns

A string representing the subject of the message

5.4.2.6 - (NSString \*) *getContent*

Get the content of the message.

## Returns

A string representing the content of the message

5.4.2.7 - (NSArray \*) *getFields*

Get the fields of the message.

## Returns

The fields of the message as a list of [MigratoryDataField](#) objects



**5.4.2.8 - (NSString \*) getClosure**

Get the closure of the message.

**Returns**

The closure data of the message

**5.4.2.9 - (bool) isSnapshot**

Test whether the message is a snapshot message or not.

**Returns**

true if the message is a snapshot message



# Chapter 6

## File Documentation

### 6.1 src/MigratoryDataClient.h File Reference

Include the declaration of the [MigratoryDataClient](#) class.

#### Classes

- class [MigratoryDataClient](#)

*This class implements all the necessary operations for connecting to a cluster of one or more MigratoryData servers, subscribing to subjects, getting real-time messages for the subscribed subjects, and publishing real-time messages.*

#### 6.1.1 Detailed Description

Include the declaration of the [MigratoryDataClient](#) class.

### 6.2 src/MigratoryDataField.h File Reference

Include the declaration of the [MigratoryDataField](#) class.

#### Classes

- class [MigratoryDataField](#)

*Represent a message field.*

#### 6.2.1 Detailed Description

Include the declaration of the [MigratoryDataField](#) class.

### 6.3 src/MigratoryDataGlobals.h File Reference

Include global constants and typedefs.

## Functions

- typedef [NS\\_ENUM](#) (NSInteger, LogType)

*This class enumerates the MigratoryData logging levels.*

## Variables

- NSString \* [NOTIFY\\_SERVER\\_UP](#)

*Indicate that the client successfully connected to a MigratoryData server.*

- NSString \* [NOTIFY\\_SERVER\\_DOWN](#)

*Indicate that the client failed to connect to a MigratoryData server.*

- NSString \* [NOTIFY\\_DATA\\_SYNC](#)

*After a failover reconnection, the client synchronized a subscribed subject with the latest message available for that subject, as well as with all messages published during the failover for that subject.*

- NSString \* [NOTIFY\\_DATA\\_RESYNC](#)

*After a failover reconnection, the client synchronized a subscribed subject with the latest message available for that subject, but not with the potential messages published during the failover, therefore behaving as a new client.*

- NSString \* [NOTIFY\\_SUBSCRIBE\\_ALLOW](#)

*Indicate that the client was authorized to subscribe to a subject.*

- NSString \* [NOTIFY\\_SUBSCRIBE\\_DENY](#)

*Indicate that the client was not authorized to subscribe to a subject.*

- NSString \* [NOTIFY\\_PUBLISH\\_DENIED](#)

*Indicate that the client was unable to publish a message because it is not allowed by your entitlement rules.*

- NSString \* [NOTIFY\\_PUBLISH\\_NO\\_SUBSCRIBER](#)

*Indicate that the client was unable to publish a message because there is no client subscribed to the subject of the message.*

- NSString \* [NOTIFY\\_PUBLISH\\_OK](#)

*Indicate that the client successfully published a message.*

- NSString \* [NOTIFY\\_PUBLISH\\_FAILED](#)

*Indicate that the client was unable to publish a message.*

### 6.3.1 Detailed Description

Include global constants and typedefs.

### 6.3.2 Function Documentation

#### 6.3.2.1 typedef NS\_ENUM ( NSInteger , LogType )

This class enumerates the MigratoryData logging levels.

The available logging levels ordered by verbosity are:

- LOG\_ERROR (less verbose)
- LOG\_INFO
- LOG\_DEBUG
- LOG\_TRACE (most verbose)

For production usage, we recommend the default `LOG_INFO` logging level. The `LOG_ERROR` level turns on the error logs of the API.

The `LOG_INFO` level turns on the info, warning, and error logs of the API.

The `LOG_DEBUG` level turns on the debug, info, warning, and error logs of the API.

The `LOG_TRACE` level turns on all the logs of the API.

### 6.3.3 Variable Documentation

#### 6.3.3.1 NSString\* NOTIFY\_SERVER\_UP

Indicate that the client successfully connected to a MigratoryData server.

This constant indicates that the client successfully connected to one of the MigratoryData servers defined with the API method [MigratoryDataClient::setServers:](#).

#### 6.3.3.2 NSString\* NOTIFY\_SERVER\_DOWN

Indicate that the client failed to connect to a MigratoryData server.

This constant indicates that the client failed to connect to one of the MigratoryData servers defined with the API method [MigratoryDataClient::setServers:](#).

#### 6.3.3.3 NSString\* NOTIFY\_DATA\_SYNC

After a failover reconnection, the client synchronized a subscribed subject with the latest message available for that subject, as well as with all messages published during the failover for that subject.

This constant indicates that the client successfully synchronized the subject provided in the detail information of the status notification. Also, the potential messages published for that subject during the failover period have been successfully retrieved at the moment of the reconnection.

#### 6.3.3.4 NSString\* NOTIFY\_DATA\_RESYNC

After a failover reconnection, the client synchronized a subscribed subject with the latest message available for that subject, but not with the potential messages published during the failover, therefore behaving as a new client.

This constant indicates that the client successfully synchronized the subject provided in the detail information of the status notification. However, the client was unable to get the messages published during the failover. Therefore, it behaves like a new client which connects to the MigratoryData server at the moment of the failover reconnection.

#### 6.3.3.5 NSString\* NOTIFY\_SUBSCRIBE\_ALLOW

Indicate that the client was authorized to subscribe to a subject.

This constant indicates that the client – identified with the token defined with the API method [MigratoryDataClient::setEntitlementToken:](#) – is allowed to subscribe to the subject provided in the detail information of the status notification.

#### 6.3.3.6 NSString\* NOTIFY\_SUBSCRIBE\_DENY

Indicate that the client was not authorized to subscribe to a subject.

This constant indicates that the client – identified with the token defined with the API method [MigratoryDataClient::setEntitlementToken:](#) – is not allowed to subscribe to the subject provided in the detail information of the status notification.

### 6.3.3.7 NSString\* NOTIFY\_PUBLISH\_DENIED

Indicate that the client was unable to publish a message because it is not allowed by your entitlement rules.

This constant is used to indicate that the publication of the message, having the closure provided in the detail information of the status notification, has failed. The publication failed because the client – identified with the token defined with the API method [MigratoryDataClient::setEntitlementToken:](#) – is not allowed to publish on the subject of the message.

### 6.3.3.8 NSString\* NOTIFY\_PUBLISH\_NO\_SUBSCRIBER

Indicate that the client was unable to publish a message because there is no client subscribed to the subject of the message.

This constant is used to indicate that the publication of the message, having the closure provided in the detail information of the status notification, has failed. The publication failed because there is no client then subscribed to the subject of the message.

### 6.3.3.9 NSString\* NOTIFY\_PUBLISH\_OK

Indicate that the client successfully published a message.

This constant is used to indicate that the publication of the message, having the closure provided in the detail information of the status notification, has succeeded.

### 6.3.3.10 NSString\* NOTIFY\_PUBLISH\_FAILED

Indicate that the client was unable to publish a message.

This constant is used to indicate that the publication of the message, having the closure provided in the detail information of the status notification, has failed.

## 6.4 src/MigratoryDataListener.h File Reference

Include the declaration of the [MigratoryDataListener](#) class.

### Classes

- protocol [<MigratoryDataListener>](#)

*Implementations of this interface can handle the real-time messages received for the subscribed subjects as well as various status notifications.*

### 6.4.1 Detailed Description

Include the declaration of the [MigratoryDataListener](#) class.

## 6.5 src/MigratoryDataMessage.h File Reference

Include the declaration of the [MigratoryDataMessage](#) class.

## Classes

- class [MigratoryDataMessage](#)  
*Represent a message.*

### 6.5.1 Detailed Description

Include the declaration of the [MigratoryDataMessage](#) class.

# Index

- <MigratoryDataListener>, 15
- dispose
  - MigratoryDataClient, 14
- getClosure
  - MigratoryDataMessage, 18
- getContent
  - MigratoryDataMessage, 18
- getFields
  - MigratoryDataMessage, 18
- getName
  - MigratoryDataField, 15
- getSubject
  - MigratoryDataMessage, 18
- getSubjects
  - MigratoryDataClient, 13
- getValue
  - MigratoryDataField, 15
- init:content:
  - MigratoryDataMessage, 17
- init:content:closure:
  - MigratoryDataMessage, 18
- init:content:fields:
  - MigratoryDataMessage, 17
- init:content:fields:closure:
  - MigratoryDataMessage, 18
- init:value:
  - MigratoryDataField, 15
- isSnapshot
  - MigratoryDataMessage, 19
- MigratoryDataClient, 9
  - dispose, 14
  - getSubjects, 13
  - pause, 13
  - publish:, 13
  - resume, 14
  - setEncryption:, 12
  - setEntitlementToken:, 13
  - setListener:, 10
  - setLogType:, 10
  - setServers:, 10
  - setServersDownBeforeNotify:, 13
  - subscribe:, 11
  - subscribeWithConflation:conflationTimeMillis:, 12
  - unsubscribe:, 12
- MigratoryDataField, 14
  - getName, 15
  - getValue, 15
  - init:value:, 15
- MigratoryDataGlobals.h
  - NOTIFY\_DATA\_SYNC, 23
  - NOTIFY\_PUBLISH\_OK, 24
  - NOTIFY\_SERVER\_UP, 23
  - NS\_ENUM, 22
- MigratoryDataListener-p
  - onMessage:, 15
  - onStatus:info:, 16
- MigratoryDataMessage, 17
  - getClosure, 18
  - getContent, 18
  - getFields, 18
  - getSubject, 18
  - init:content:, 17
  - init:content:closure:, 18
  - init:content:fields:, 17
  - init:content:fields:closure:, 18
  - isSnapshot, 19
- NOTIFY\_DATA\_RESYNC
  - MigratoryDataGlobals.h, 23
- NOTIFY\_DATA\_SYNC
  - MigratoryDataGlobals.h, 23
- NOTIFY\_PUBLISH\_OK
  - MigratoryDataGlobals.h, 24
- NOTIFY\_SERVER\_DOWN
  - MigratoryDataGlobals.h, 23
- NOTIFY\_SERVER\_UP
  - MigratoryDataGlobals.h, 23
- NS\_ENUM
  - MigratoryDataGlobals.h, 22
- onMessage:
  - MigratoryDataListener-p, 15
- onStatus:info:
  - MigratoryDataListener-p, 16
- pause
  - MigratoryDataClient, 13
- publish:
  - MigratoryDataClient, 13
- resume
  - MigratoryDataClient, 14
- setEncryption:
  - MigratoryDataClient, 12
- setEntitlementToken:
  - MigratoryDataClient, 13



setListener:  
    MigratoryDataClient, [10](#)

setLogType:  
    MigratoryDataClient, [10](#)

setServers:  
    MigratoryDataClient, [10](#)

setServersDownBeforeNotify:  
    MigratoryDataClient, [13](#)

src/MigratoryDataClient.h, [21](#)

src/MigratoryDataField.h, [21](#)

src/MigratoryDataGlobals.h, [21](#)

src/MigratoryDataListener.h, [24](#)

src/MigratoryDataMessage.h, [24](#)

subscribe:  
    MigratoryDataClient, [11](#)

subscribeWithConflation:conflationTimeMillis:  
    MigratoryDataClient, [12](#)

unsubscribe:  
    MigratoryDataClient, [12](#)